

## 8" Two-Way In-Wall Loudspeaker



# RCW-5

Sophisticated design, premium materials, and exceptional performance make Reference Series architectural speakers the logical choice where smooth, clear highs, solid bass, and total reliability are as important as stealth. The easy-to-install RCW-5 makes the case perhaps better than any other, delivering the sort of big, gutsy sound not normally associated with in-walls. It works extremely well in high-end distributed-sound systems, multi-room home music systems, and low-visual-impact home theater installations — any application where you need really good loudspeakers to be heard but not seen. And because they share so many design elements with our freestanding Reference Series speakers, their sound blends perfectly in mixed systems, giving you maximum flexibility.

An 8-inch Cerametallic™ cone woofer with a cast-polymer frame gives the RCW-5 impressive bass extension and output capability. The titanium dome compression driver tweeter is mated to a 6-inch square 90° x 60° Klipsch Tractrix® Horn that can be pivoted to focus the sound where it's needed, which is a great benefit when the speaker must be mounted in a less-than-ideal location. Tweeter and midbass attenuation switches give an added measure of control in tailoring the speaker's output to the acoustics of its environment.

The RCW-5's flush-mount white frame and rustproof, powder-coated aluminum grille can be painted to blend into the wall; an IR punchout accommodates standard infrared receivers. Superior components and construction ensure long, trouble-free service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- Very high sensitivity and power handling
- Durable cast-polymer frame with shallow 3.75" mounting depth
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Treble and midbass attenuation switches and IR receiver punchout
- Frame and rustproof aluminum grille paintable to match wall

## SPECIFICATIONS

BANDWIDTH	38Hz-20kHz ± 3dB
SENSITIVITY	94dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2500Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) titanium diaphragm compression driver tweeter with pivoting 90° x 60° Tractrix Horn and one 8" (20.3cm) Cerametallic cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	6 lbs. (2.7kg)
HEIGHT	15.8" (40.1cm)
WIDTH	10.2" (25.9cm)
MOUNTING DEPTH	3.75" (9.5cm)
CUTOUT DIMENSIONS	14.8" (37.6cm) x 9.3" (23.6cm)
FINISH	White
INSTALLATION KIT	W-800-IK

Suggested Retail: \$799/Pair



www.klipsch.com  
1-800-KLIPSCH